**Test Certificate of** Cable Spiking Test

Medium voltage network rail power cables **Apparatus** 

Cu/XLPE/CWS/PE/graf 19/33/36 1x300/50 mm<sup>2</sup> (metallic screen diameter of copper **Designation** 

wire:1,35 mm)

Nominal voltage 19/33 kV; maximum voltage 36 kV; Rated frequency 50 Hz;

Rated short-circuit current of screen for 1 sec: 11 kA

Manufacturer ELKA Kabeli – Zagreb, Kroatia **Tested for** ELAND Cables - London, UK

Date(s) of tests from June 28, 2007

CESI S.p.A. - Milano - ITALY Tested by

The apparatus, constructed in accordance with the description, drawings and photographs incorporated in the reference documents, identified in this certificate, has been subjected to the series of proving tests in accordance will

> Appendix C of Network Rail specification N PS/ELP/00008 rev.3(2005) and Table par. 6.1 of NG/Gn/ELP/27283 rev.1(2005)

This Test Certificate has been issued by CESI in accordance with above mentioned Standards.

The results are shown in the record of Proving Tests and the oscillograms attached in the Test Reports. The values obtained and the general performance are considered to comply with the above Standards and to justify the ratings assigned by the Manufacturer as listed on page No.2.

The Certificate applies only to the apparatus tested. The esponsibility for conformity of any apparatus having the same designations with that tested rests with the Manufacturer

Only integral reproduction of this Certificate, or reproductions of this page accompanied by any pages on which are stated the endorsed ratings of the apparatus tested, are permit ed without written permission from CESI.

No. of pages

Issue date July 9, 2007

**Prepared** Unit LABORATORIES - U. Vercellotti

Verified Unit LABORATORIES - G. Arneodo

**Approved** Area COMPONENTS - V. Scarioni Technical Area Components ting Laboratories"